



ROSSINI

Automatic balancing system for grinding wheels



The correct balancing of the shaft and grinding wheel assembly is a basic operation for ensuring the right surface quality becoming a milestone to achieve excellent results with grinding rubbers or techno-polymers and to dramatically improve the life of the rotational parts (bearings, shaft, motor and grinding wheel). The dynamic balancing system continuously active during the grinding process and assembled on the external side of the mandrel is now available for the grinding machine of Rossini Prima Grinder also as retrofit application on existing machines. For further info please contact Rossini.

Rossini S.p.A. provides no warranties that the contents of this document demonstrate, in particular, the fitness of the products it contains for any specific purpose; we therefore ask customers to verify in advance that the product's characteristics are suitable for its intended use. Rossini S.p.A. reserves the right to update this publication and periodically modify its contents, including technical/commercial information, without further notice of the amendments or changes made. This document and any logos, trademarks and specifications etc. it contains are protected by copyright laws with all rights reserved.



Rossini World
Italy • France • Spain
Germany • United Kingdom
Romania • Brasil • China
United States • India

Rossini S.p.A. HeadQuarters
Via de Gasperi, 5
20027 Rescaldina - Milano - Italy
Tel. +39 0331 47 27 11 - Fax +39 0331 57 97 46
comm.dept@rossini-spa.it

WWW.ROSSINI-SPA.IT